

QDLASER

QLF1339-AA

1310 nm FP LASER TO-CAN

C00042-03 Nov. 2015



1. DESCRIPTION

The QLF1339-AA is 1310 nm quantum dot laser diode device for use in telecom and datacom applications up to 2.5Gbps speed. The laser is mounted into a TO-56 header without PD monitor and hermetic sealed with a lens cap. Since quantum dot technologies are equipped with active layers of the device, it realizes excellent temperature characteristics and low power consumptions.

2. FEATURES

- 1310 nm FP-LD
- $\Phi 5.6\text{mm}$ TO-CAN package
- Wide temperature operation: -10 to 85 deg.C
- PD less type

3. APPLICATION

- Optical communication

4. ABSOLUTE MAXIMUM RATING

($T_c = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATING	UNIT
Light Output Power	P_o	6	mW
LD Forward Current	I_F	80	mA
LD Reverse Voltage	V_{RLD}	2	V
Operation Temperature (T_c)	T_c	-10 to 85	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to 100	$^\circ\text{C}$
Lead Soldering Temperature (5 s)	T_{sld}	230	$^\circ\text{C}$

5. OPTICAL AND ELECTRICAL CHARACTERISTICS




(T_c = 25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	T _c	MIN	TYP	MAX	UNIT
Threshold current	I _{th}	CW	-10°C	-	8	15	mA
			25°C				
			85°C				
Operation current	I _{op}	CW, P _o =5 mW	-10°C	-	28	40	mA
			25°C				
			85°C				
Operation voltage	V _{op}	CW, P _o =5 mW	-10°C	-	1.4	1.6	V
			25°C				
			85°C				
Slope efficiency	η	CW	-10°C	0.23	0.28	-	W/A
			25°C				
			85°C				
Saturation power	P _{sat}	CW	85°C	6	-	-	mW
Center wavelength	λ _c	CW, P _o =5 mW	-10°C	1275	1289	1345	nm
			25°C		1305		
			85°C		1335		
Spectral width	□λ	CW, P _o =5 mW RMS(-20dB)	-10°C	-	2.9	4.0	nm
			25°C		2.6		
			85°C		2.1		
Rise and fall time	T _r , T _f	I _b = I _{th} , P _o =5 mW, 10-90%	25°C	-	0.05	-	nsec
Optical power coupled to fiber	P _f	CW, P _o =5 mW, SI10/125	25°C	-	0.85	-	mW
Focal length	D _f	CW, P _o =5 mW, SI10/125	25°C	-	6.25	-	mm
Ray Axis	θ _{xy}	CW, P _o =5 mW	25°C	-	0	-	deg.
Beam angle	θ _z	CW, P _o =5 mW	25°C	-	1.1	-	deg.

QDLASER


QLF1339-AA

C00042-03



Typical characteristics

6. Outline Drawing



7. Notice

- Safety Information

This product is classified as Class 1M laser product, and complies with 21 CFR Part 1040.10.

Please do not take a look laser lighting in operations since laser devices may cause troubles to human eyes.

Please do not eat, burn, break and make chemical process of the products since they contain GaAs material.

- Handling products


Semiconductor lasers are easily damaged by external stress such as excess temperature and ESD.

Please pay attention to handling products, and use within range of maximum ratings.

QD Laser takes no responsibility for any failure or unusual operation resulting from improper handling, or unusual physical or electrical stress.

- RoHS

This product conforms to RoHS compliance related EU Directive 2011/65/EU.



QD Laser, Inc.

Contact : info@qdlaser.com <http://www.qdlaser.com>

Copyright 2010-2015 All Rights Reserved by QD Laser Inc.

Address : Keihin Bldg.1F 1-1 Minamiwataridacho, Kawasaki-ku, Kawasaki, Kanagawa Zip 210-0855 Japan

All company or product names mentioned herein are trademarks or registered trademarks of their respective owners. Information provided in this data sheet is accurate at time of publication and is subject to change without advance notice.