


# THEIA Diode-Pumped Nd: YAG Laser Series

Designed for industrial applications  
High reliability & lifetime  
High energy &  
High average power



# THEIA

## Diode-Pumped Solid State Laser

### Applications

- Laser shock peening
- Laser adherence testing
- Laser annealing
- Laser lift-off
- Laser cleaning
- Pumping of TeraWatt TiSa amplifiers

### Features and Benefits

- High energy (Joule class) and high average power (>100 W) from the same laser beam
- Performance suited to the most demanding industrial applications
- Reliable solution to use in manufacturing process
- Low operation and maintenance costs
- Long lasting pumping diodes

### Physical characteristics

#### Power supply

20.9 x 22 x 31.1 in      65 x 60 x 83 cm

#### Cooling unit

14.6 x 17.4 x 28.4 in      37 x 44 x 72 cm

#### Laser Head




63 x 11.34 x 7.4 in      160 x 28.8 x 18.8 cm

### Specifications

MODEL	THEIA
Repetition Rate (Hz)	Up to 200
Energy per pulse (mj)	
-> At 1064 nm	≥ 1000
-> At 532 nm	≥ 700
-> At 355 nm	≥ 500
Pulse to pulse energy stability (% rms)	< 1
Typical pulse duration (ns)	10

### Utilities and environment requirements

Voltage	230 VAC ± 5% Single phase	
Frequency	50 – 60 Hz	
Water Flow	> 2.7 gal/min	>10 L/min
Static pressure	43.5 – 72 psi	3 – 5 bars
Temperature	15 – 17 °C	



Thales LAS France SAS – 2, avenue Gay-Lussac – 78990 Élancourt – FRANCE

Tél: + 33 (0)1 30 96 70 00 > thalesgroup.com < [in](#) [tw](#) [f](#) [yt](#)

thales-laser@fr.thalesgroup.com – www.thalesgroup.com/en/lasers